SERVICE-HOTLINE +49 375 2795 123

Asphalt Adhesive Sprayer

asphalt adhesive | sprayer | pressurised container | spray on



Short information

- for precise and energy-saving distribution of BORNIT® Asphalt Adhesive C40BF5-S on all kinds of small construction sites
- pressure vessel with a capacity of 18 litres
- spraying capacity of up to 90 m2 with one filling

Consumption

- approx. 0.20 - 0.45 kg/m2 BORNIT® Asphalt Adhesive C40BF5-S; up to 90 m2 with one filling

Storage note

- store dry
- protect from frost
-

Complementary products

Cleaning

- BORNIT® MultiClean
- BORNIT® MultiClean Spray
- BORNIT® Bitumen Cleaner

Follow-up products

- BORNIT® Asphalt Adhesive R2 C40BF5-S
- BORNIT® Valve for Asphalt Adhesive Sprayer

Content	Item	EAN code	Colour	sufficient for:
1 piece / unpacked	6800000935	4 017228 00887 5	light-grey	up to 90 m2 with one filling

Areas of application

The BORNIT® Asphalt Adhesive Sprayer is the indispensable tool for precise and energy-saving distribution of bitumen emulsion C40BF5-S (Asphalt Adhesive) or R2 C40BF5-S on all types of small construction sites. The well thought-out design scores with great ease of use and high utility value. The pressure tank has a usable capacity of 18 litres and can be completely emptied with a single charge of compressed air. This results in a spraying capacity of up to 90 m2 with one filling.

Product data in brief

Product type	pressure sprayer
Base	pressure tank, spiral hose and spraying lance
colour(s)	light-grey
storage	store dry protect from frost
Atomising lance	600 mm
Length spiral hose	5 m with 360° rotatable coupling
Pressure gauge	6 - 8 bar operating pressure
Compressed air connection	KSG 1/4" NW7
Capacity	18 litres
Vessel size	24 litres
Operating temperature	max. +40 °C
Operating pressure	6 - 8 bar
Empty weight	approx. 11 kg
Dimension (LxWxH)	330 x 780 x 280 mm

Type and properties

Used for application of BORNIT® Asphalt Adhesive C40BF5-S or R2 C40BF5-S. The practical 25 kg adhesive canister from BORNIT® and the range of accessories for use with truck compressed air or via car valve set no limits to the application range of the Asphalt Adhesive sprayer.

Consumption

approx. 0.20 - 0.45 kg/m2 BORNIT® Asphalt Adhesive C40BF5-S; up to 90 m2 with one filling

Health and fire protection, occupational safety

To ensure safe handling of the product, the physical, safety, toxicological and ecological information provided online, the information in the current operating instructions and the additional information on the label must be read and followed before purchasing or using the product! The applicable regulations, ordinances and laws must be complied with.

In case of doubt, please contact the BORNIT® application technology department or the BORNIT® service hotline on +49 375 2795 123.

Warning notices

Note

This data sheet supersedes all previous technical information relating to the product. Such information is therefore no longer valid. The details have been compiled in accordance with the latest state of the art in application technology. Please note, however, that depending on the condition of the building, it may be necessary to deviate from the working methods recommended in this data sheet. Unless otherwise agreed in an individual contract, all information contained in this data sheet is non-binding and therefore does not constitute an agreed product specification. We reserve the right to make changes to the information contained in this data sheet at any time. We recommend that you check our website www.bornit.de for any updates.

The product illustrations are to be regarded as examples. No legally binding claim can be derived from them. We reserve the right to make changes to the product's appearance.

Our packaging complies with the relevant legal requirements and with Regulation (EU) 2025/40 on packaging and packaging waste (PPWR). The technical documentation in accordance with Annex VII is available and can be provided on request by emailing info@bornit.de.